

Cable bucket

For all excavators in the 1.5–27 tonne weight classes

Engcon's cable bucket – developed for precision excavation with minimal width for e.g. cables or other services requiring narrow trenches. Its deep profile means better accessibility beneath intersecting cables and pipes and also allows deep trenching without the need for the tiltrotator to go below surface level.

Engcon's cable buckets are available in two models – Standard and tapered (C)

Standard is the conventional type with parallel side plates for excavating ditches with vertical sides.

The tapered model has a narrower blade than the standard cable bucket but with the same width top, producing a narrower trench bottom with slightly sloping sides.

Engcon's cable buckets are made from high-quality steel. As with other Engcon buckets, the cutters and other exposed wear surfaces have a hardness of 500 Brinell.



Standard



Conical

A factory-fitted tooth kit is available as an optional extra.



Tooth kit, type Cat

Specifications

Model	CB01	CB03	CB03	CB05	CB05	CB08	CB10	CB15	CB15C	CB20	CB20	CB25	CB25
Volume: (l)	35	90	90	130	130	155	160	350	260	400	400	550	550
Width: (mm)	240	290	290	340	340	400	460	560	300	660	660	600	600
Weight: (kg)	25	55	55	70	85	95	160	290	255	320	360	590	615
Quick hitch standard:	S30	S30	S40	S40	S45	S45	S45	S60	S60	S60	S70	S70	S80
Base machine weight (t)	1,5–2	2–4	2–4	4–6	4–6	6–10	8–13	13–17	13–17	17–22	17–22	22–27	22–27

CHANGE THE WORLD OF DIGGING

engcon Ireland Ltd. | Bellview, 1 Station Road, Leixlip, co. Kildare, W23 N6C6
 Phone +353 15 686 742 | E-mail ireland@engcon.com | Web engcon.com